

# Avery Weigh-Tronix

## QC3265 Checkweigher Medium Capacity



*Shown with optional  
E1010 indicator*

Quick Check, the new Model QC3265 Checkweigher from Avery Weigh-Tronix, combines rugged stainless steel construction with the proven accuracy of Weigh Bar® weight sensors.



# QC3265 Checkweigher – Medium Capacity

## Features and benefits

**NEMA 4 stainless steel display** – Quick Check is washdown safe and built for tough environments.

**Two display modes** – Quick Check operates in Weighing Mode with a simple weight display or in Checkweighing Mode with added LEDs for Over, Under, and Accept.

**Simple setup** – A single keystroke accomplishes most of the setup functions. Change target values, over and under tolerances, even units of measure in seconds.

**Simple operation** – Uncluttered display matches the Quick Check's no-nonsense operation. Just three control keys mean short training time and minimal opportunity for human error.

**Five units of measure** – Select to read in pound, ounces, kilograms, grams or pounds/ounces for added versatility.

**Single Weigh Bar® design** – No moving parts for low maintenance. Proven resistance to washdown. Suitable for food processing environments.

## Options

- Tower mounted toggle switch for setting zero and target values.
- 230 VAC 50/60 Hz power
- Built-in 30-hour battery and charger (LCD version only)
- RS-232 or RS-485 interface board
- Remote display and base (includes wall-mount bracket)
- Substitute Indicator Model WI-125, E1010, E1070

## Specifications

### Capacities and increments:

| Pounds     | Ounces     | Kilograms  | Grams        |
|------------|------------|------------|--------------|
| 100 x 0.02 | 1600 x 0.5 | 50 x 0.01  | 50,000 x 10  |
| 200 x 0.05 | 3200 x 1.0 | 100 x 0.02 | 100,000 x 20 |
| 500 x 0.1  | 8000 x 2   | 220 x 0.05 | N/A          |

### Overall dimensions:

**100-lb scale:** 20" W x 27" D x 35" H (51 cm x 68 cm x 89 cm)  
**200 & 500-lb scale:** 24" W x 31" D x 35" H (61 cm x 78 cm x 89 cm)

### Weighing surface dimensions:

**100-lb scale:** 20" x 20" (51 cm X 51 cm)  
**200 & 500-lb scale:** 24" X 24" (61 cm X 61 cm)

### Display:

LCD – 7-segment, 6-digit, 0.7" high  
LED – 7-segment, 6-digit, 0.6" high  
8 annunciators for Over, Accept, Under, lb, kg, oz, g, lb/oz and Center Zero

### Controls:

TARGET – Enters target weight  
UNITS – Changes enabled units of measure  
ZERO – Zero balances the scale

**Overload protection:** 150% of scale capacity

**Corner load:** 100% of scale capacity

### Construction:

Stainless steel, NEMA 4X electronics enclosure  
Stainless steel scale shroud and understructure  
Plated and encapsulated Weigh Bar®

### Environment:

14° to 104°F (-10° to 40°C) Water washdown

**Display-to-loadcell cable length:** 10 feet

### Power:

**Standard:** 115 VAC, ±10%  
50/60 Hz, 10 watts max  
Power cord length, 6 feet (1.8 meters)  
**Optional:** 230 VAC (±10) 50/60 Hz, 15 watts max.

### Agencies:

USDA approval  
NTEP approval  
UL



## AUTHORIZED DISTRIBUTORS

### Ask the experts.

Weigh-Tronix distributors are complete support centers, providing needs assessment, technical information, product sales and service. Their experience is a valuable resource that is readily available to you. We recommend you consult these knowledgeable industrial applications specialists for all of your weight measurement needs.

Please call us or visit  
[www.wtxweb.com](http://www.wtxweb.com)  
for your nearest  
Weigh-Tronix distributor.

## Avery Weigh-Tronix

Fairmont, Minnesota U.S.A.  
USA Toll-Free: 800-368-2039  
USA Phone: 507-238-4461  
[www.wtxweb.com](http://www.wtxweb.com)

Pointe Claire, Quebec Canada  
CAN Toll-Free: 800-561-9461  
CAN Phone: 514-695-0380  
[www.weigh-tronix.ca](http://www.weigh-tronix.ca)

